

**KP1H-20**

Gear grease for power tools VP 820

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL mineral oil**THICKENER** sodium**VISCOSITY** 220 mm²/s**OPERATING TEMPERATURE** -20 °C bis 100 °C**NLGI CLASS** 1**FIELD OF USE**

- transmission

BUSINESS

- Power Tools

FUNCTIONALITY

- fluid grease

PACKING

- 250 g tube
- 400 g cartridge

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr****ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH**Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 150 kg barrel
-

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com