KP2K-20

Fluid gear grease for power tools VP 728

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL mineral oil

THICKENER sodium

VISCOSITY 320 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 00

FIELD OF USE

- transmission
- roller bearing
- bearings

BUSINESS

- Power Tools

FUNCTIONALITY

- fluid grease

PACKING

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com