

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



H1-Grease for low temperatures LFC 900 AC H1 Halal



ELKALUB LFC 900 AC is an anti-corrosion oil for temporary preservation (e.g., transport preservation) of machines and machine parts. ELKALUB LFC 900 AC is NSF H1-registerable; use on machines and machine parts for the food industry or other hygiene-sensitive industrial areas is therefore a preferred application. The corrosion protection of ELKALUB LFC 900 AC was assessed in the laboratory and in practical tests (shipping overseas, weathering tests). Due to different machine materials, preservation methods and transport conditions, company-specific tests are recommended before use. ELKALUB LFC 900 AC can be applied by dipping, brushing or spraying. Due to the content of less soluble anti-corrosion components, the oil should be stirred before use.

BASE OIL Other

OPERATING TEMPERATURE 10 °C bis 25 °C

VISCOSITY AT 40 °C 45 mm²/s

PACKING

- 750 ml /1 l
- 5 l canister

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach bestem Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com