



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFHC2N-20

high-load grease VP 873 H1 Halal



ELKALUB VP 873 is a grease for heavily loaded roller bearings (especially tapered and spherical roller bearings, cam rollers).

Due to the high load-bearing capacity and the high wear protection, **ELKALUB VP 873** is also used as a lubricant in open gears. The lubrication points benefit from the adhesive formulation, which is also responsible for a high level of corrosion protection and water resistance.

The addition of solid lubricants supports sliding pairings and ensures emergency running properties.

ELKALUB VP 873 is suitable for metal-plastic combinations. Due to the diversity of plastic materials, a previous resistance test is recommended.

A special application of **ELKALUB VP 873** is as an assembly paste for stainless steel screw connections in the food industry. The grease prevents cold welding.

BASE OIL White oil Other

THICKENER polyurea solid lubricants

VISCOSITY 460 mm²/s

OPERATING TEMPERATURE -20 °C bis 140 °C

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

NLGI CLASS 1 - 2

FIELD OF USE

- roller bearing
- bearings
- open gears
- racks
- Guides & Curves

BUSINESS

- Food
- beverages
- Pharma & Medicine
- drive technology
- bearing manufacturer

FUNCTIONALITY

- assembly grease
- High temperature grease
- Food grease
- Against tribocorrosion
- lubricant

PACKING

- 250 g tube
 - 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com