

# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**



## High-performance mineral oil LFC 1320

ELKALUB EP-high-performance lubricating oils based upon mineral oil are ready-for-use lubricants with special ELKALUB additivation. They offer high protection against wear and corrosion and an excellent load carrying ability. Special inhibitors against ageing assure a long service life and safe operation. They should be used according to the viscosity prescriptions of the machine manufacturers. All oils of the ELKALUB LFC 1000 group are exempt from PCB and chlorine products and can be disposed of as normal used oils.

**BASE OIL** ester mineral oil

---

**OPERATING TEMPERATURE** -10 °C bis 120 °C

---

**VISCOSITY AT 40 °C** 320 mm<sup>2</sup>/s

---

### FIELD OF USE

- transmission
  - roller bearing
  - bearings
- 

### PACKING

- 1 liter can
  - 5 l jug
  - 20 l jug
  - 200 l barrel
- 

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com