



Mounting Paste ELKALUB 22103

ELKALUB 22103 is an assembly paste to prevent tribocorrosion and fretting corrosion. The high percentage of solid lubricants results in pressure-resistant and permanent lubrication of the metal surface; shaft-hub connections, bearings, flanges and other strongly fixed machine parts can be reliably dismantled.

ELKALUB 22103 is suitable for lubrication in the high temperature range up to 700 °C. The polyglycol oil ensures lubrication up to approx. 200 °C; above this temperature the solid inorganic thickener takes over.

ELKALUB 22103 can be registered as NSF H1 lubricant and is therefore suitable for use in the food sector or related industries (pharmaceuticals, animal feed, packaging).

BASE OIL polyglycol

THICKENER Inorganic

VISCOSITY 400 mm²/s

OPERATING TEMPERATURE -30 °C bis 700 °C

NLGI CLASS 1

FUNCTIONALITY

- assembly grease
- High temperature grease

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com