



ELKALUB

Hochleistungs-Schmierstoffe
High Performance Lubricants



KPPG2P-30

Polyglycol grease VP 878

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL polyglycol

THICKENER Lithium complex

VISCOOSITY 60 mm²/s

OPERATING TEMPERATURE -30 °C bis 150 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings

BUSINESS

- Automotive
- bearing manufacturer

FUNCTIONALITY

- Low-temperature grease

PACKING

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr



ELKALUB

Hochleistungs-Schmierstoffe
High Performance Lubricants

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com