



KPPG2K-30

polyglycol grease GLS 886/N2 H1 Halal



ELKALUB GLS 886/N2 is a polyglycol grease that can be used for the lubrication of roller and plain bearings as well as the lubrication of smaller gears with a high proportion of sliding friction (e.g. worm gears).

The slight dissolving properties of ELKALUB GLS 886/N2 in relation to UV light curing products (paint, varnish, adhesives) keep lubrication points mobile.

This applies, for example, to printing machines with UV dryers and the lubrication of cam rollers and gripper shaft bearings.

In another application, ELKALUB GLS 886/N2 can be used as an assembly aid for EPDM materials.

The compatibility with other materials and the miscibility with mineral oil-based products must be checked before use.

ELKALUB GLS 886/N2 is NSF H1 registered and can therefore be used in the food industry and related hygiene-sensitive areas (pharmaceuticals, packaging, animal feed).

Former product name: VP 886

BASE OIL polyglycol

THICKENER Inorganic

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

VISCOSITY 180 mm²/s

OPERATING TEMPERATURE -30 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
 - bearings
 - Fittings & O-rings
-

BUSINESS

- print
 - Food
 - beverages
 - Pharma & Medicine
 - bearing manufacturer
-

FUNCTIONALITY

- Food grease
-

PACKING

- 250 g tube
 - 100 g cartridge
 - 380 g LubeShuttle
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com