



PTFE spray FLC 9025 H1 Halal



ELKALUB FLC 9025 H1 PTFE spray is an Synthetic oil spray with PTFE. Excellent sliding lubrication properties, highest wear protection and emergency running properties thanks to solid lubricants. For guides, joints, shafts and bushings and other sliding elements. With H1 registration for use in the food and pharmaceutical industries.

BASE OIL Poly-alpha-olefin

OPERATING TEMPERATURE -40 °C bis 160 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 58 mm²/s

FIELD OF USE

- bearings
- Guides & Curves
- bed ways

BUSINESS

- Food
- Pharma & Medicine

FUNCTIONALITY

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Food grease
- Lubricant / release agent
- corrosion protection
- universal

PACKING

- 400 ml of aerosol
-

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com