



KPF2U-20

Wheel hubs paste VP 910

ELKALUB VP 910 was developed for the lubrication of wheel hubs, rim flanks and centering rings. **ELKALUB VP 910** guarantees easy disassembly of wheel after long periods and stubborn winters.

Lubrication points:

- Centering rings (material pairing: plastic-metal)
- Rims support surface
- Wheel hubs

Characteristics:

- A high level of corrosion protection
- Temperature Stable • Withstands splash water successfully
- High adherence

Application:

With the brush can, **ELKALUB VP 910** can be applied thinly and evenly to the surface to be lubricated.

Note:

The product must not be applied to the friction surfaces of the brake system! It is also not recommended to lubricate the thread of the wheel hub bolts. If rusty threads are cleaned when changing the wheel, we recommend our rust remover **ELKALUB FLC 1040**.

As a grease: Temperature range: -20 °C to 150 °C

As a separating paste: temperature range: -20°C to 1200 °C

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BASE OIL mineral oil

THICKENER Inorganic solid lubricants

VISCOSITY 460 mm²/s

OPERATING TEMPERATURE -20 °C bis 1200 °C

NLGI CLASS 1-2

BUSINESS

- Automotive
 - plant construction
-

FUNCTIONALITY

- assembly grease
 - High temperature grease
 - Against tribocorrosion
-

PACKING

- 200 ml brush box
 - 1 kg can
 - 150 kg barrel
-

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com