



## Bearer ring oil VP 785

ELKALUB VP 785 has been specially developed for the lubrication of cylinder bearings in printing presses. The product offers a high protection against corrosion, does not lead to and has varnish dissolving properties. Furthermore, ELKALUB VP 785 can be used as universal EP-concentrate for the lubrication of highly charged machinery elements. In order to make best use of the product's EP-properties, we recommend to apply the ELKALUB VP 785 in the temperature range from approx. +20 °C up to +80 °C.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

**BASE OIL** mineral oil

**OPERATING TEMPERATURE** -20 °C bis 120 °C

**VISCOSITY AT 40 °C** 43 mm<sup>2</sup>/s

**FIELD OF USE**

- Schmitz rings

**BUSINESS**

- print

**PACKING**

- 1 liter can
- 5 l jug

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)